

# CR 19

## TYPE

Sintered

## EDGE

Closed

## APPLICATION

High-performance diamond blades for tiles, ceramic, slate, limestone, and stone (wet cutting for ceramic)

## QUALITY

available in Professional (P) or Standard (S)

## SAFETY SIGNS



DIMENSIONS MM	DIMENSIONS INCH	MAX SPEED	MAX RPM	SEGMENT NO.	SEGMENT THICKNESS	SEGMENT HEIGHT	QUALITY
100 x 16	4 x 5/8	80 m/s	15,300	CR	1,8	7	S
100 x 16	4 x 5/8	80 m/s	15,300	CR	1,8	7	P
100 x 16	4 x 5/8	80 m/s	15,300	CR	1,8	8	S
100 x 16	4 x 5/8	80 m/s	15,300	CR	1,8	8	P
100 x 16	4 x 5/8	80 m/s	15,300	CR	1,8	10	S
100 x 16	4 x 5/8	80 m/s	15,300	CR	1,8	10	P
125 x 22	5 x 7/8	80 m/s	12,250	CR	1,9	7	S
125 x 22	5 x 7/8	80 m/s	12,250	CR	1,9	7	P
125 x 22	5 x 7/8	80 m/s	12,250	CR	1,9	8	S
125 x 22	5 x 7/8	80 m/s	12,250	CR	1,9	8	P
125 x 22	5 x 7/8	80 m/s	12,250	CR	1,9	10	S
125 x 22	5 x 7/8	80 m/s	12,250	CR	1,9	10	P
150 x 22	6 x 7/8	80 m/s	10,200	CR	1,9	7	S
150 x 22	6 x 7/8	80 m/s	10,200	CR	1,9	7	P
150 x 22	6 x 7/8	80 m/s	10,200	CR	1,9	8	S
150 x 22	6 x 7/8	80 m/s	10,200	CR	1,9	8	P
150 x 22	6 x 7/8	80 m/s	10,200	CR	1,9	10	S
150 x 22	6 x 7/8	80 m/s	10,200	CR	1,9	10	P
180 x 22	7 x 7/8	80 m/s	8,500	CR	2,2	7	S
180 x 22	7 x 7/8	80 m/s	8,500	CR	2,2	7	P
180 x 22	7 x 7/8	80 m/s	8,500	CR	2,2	8	S
180 x 22	7 x 7/8	80 m/s	8,500	CR	2,2	8	P
180 x 22	7 x 7/8	80 m/s	8,500	CR	2,2	10	S
180 x 22	7 x 7/8	80 m/s	8,500	CR	2,2	10	P
230 x 22	9 x 7/8	80 m/s	6,650	CR	2,4	7	S

For more information please scan this code with your QR Code Reader.



**KEDAS**<sup>®</sup> Professional Technology Development

**THE EXPERTS FOR HIGH QUALITY CUTTING AND GRINDING DISCS**



# CR 19

## TYPE

Sintered

## EDGE

Closed

## APPLICATION

High-performance diamond blades for tiles, ceramic, slate, limestone, and stone (wet cutting for ceramic)

## QUALITY

available in Professional (P) or Standard (S)

## SAFETY SIGNS



DIMENSIONS MM	DIMENSIONS INCH	MAX SPEED	MAX RPM	SEGMENT NO.	SEGMENT THICKNESS	SEGMENT HEIGHT	QUALITY
230 x 22	9 x 7/8	80 m/s	6,650	CR	2,4	7	P
230 x 22	9 x 7/8	80 m/s	6,650	CR	2,4	8	S
230 x 22	9 x 7/8	80 m/s	6,650	CR	2,4	8	P
230 x 22	9 x 7/8	80 m/s	6,650	CR	2,4	10	S
230 x 22	9 x 7/8	80 m/s	6,650	CR	2,4	10	P
250 x 25.4	10 x 1	100 m/s	7,650	CR	3	7	S
250 x 25.4	10 x 1	100 m/s	7,650	CR	3	7	P
250 x 25.4	10 x 1	100 m/s	7,650	CR	3	8	S
250 x 25.4	10 x 1	100 m/s	7,650	CR	3	8	P
250 x 25.4	10 x 1	100 m/s	7,650	CR	3	10	S
250 x 25.4	10 x 1	100 m/s	7,650	CR	3	10	P
300 x 20	12 x 3/4	100 m/s	6,400	CR	3,2	7	S
300 x 20	12 x 3/4	100 m/s	6,400	CR	3,2	7	P
300 x 22	12 x 7/8	100 m/s	6,400	CR	3,2	7	S
300 x 22	12 x 7/8	100 m/s	6,400	CR	3,2	7	P
300 x 25.4	12 x 1	100 m/s	6,400	CR	3,2	7	S
300 x 25.4	12 x 1	100 m/s	6,400	CR	3,2	7	P
300 x 25.4	12 x 1	100 m/s	6,400	CR	3,2	8	S
300 x 25.4	12 x 1	100 m/s	6,400	CR	3,2	8	P
300 x 25.4	12 x 1	100 m/s	6,400	CR	3,2	10	S
300 x 25.4	12 x 1	100 m/s	6,400	CR	3,2	10	P
350 x 25.4	14 x 1	100 m/s	5,500	CR	3,2	7	S
350 x 25.4	14 x 1	100 m/s	5,500	CR	3,2	7	P
350 x 25.4	14 x 1	100 m/s	5,500	CR	3,2	8	S
350 x 25.4	14 x 1	100 m/s	5,500	CR	3,2	8	P

For more information please scan this code with your QR Code Reader.



**KEDAS**<sup>®</sup> Professional Technology Development

**THE EXPERTS FOR HIGH QUALITY CUTTING AND GRINDING DISCS**



# CR 19

## TYPE

Sintered

## EDGE

Closed

## APPLICATION

High-performance diamond blades for tiles, ceramic, slate, limestone, and stone (wet cutting for ceramic)

## QUALITY

available in Professional (P) or Standard (S)

## SAFETY SIGNS



DIMENSIONS MM	DIMENSIONS INCH	MAX SPEED	MAX RPM	SEGMENT NO.	SEGMENT THICKNESS	SEGMENT HEIGHT	QUALITY
350 x 30	14 x 1 3/16	100 m/s	5,500	CR	3,2	10	S
350 x 30	14 x 1 3/16	100 m/s	5,500	CR	3,2	10	P

For more information please scan this code with your QR Code Reader.



**KEDAS**<sup>®</sup> Professional Technology Development

**THE EXPERTS FOR HIGH QUALITY CUTTING AND GRINDING DISCS**

